

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name:** PROV 500**Product code:** 40299**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet****Company name:** Proventure Solutions Ltd

Lakeside

Wanes Blades Road

Lathom

Ormskirk

L40 4BN

England

Tel: 01704 897 015**Email:** sales@proventure.co.uk**1.4. Emergency telephone number****Emergency tel:** 01704 897 015

(office hours only)

Section 2: Hazards identification**2.1. Classification of the substance or mixture****Classification under CHIP:** Xn: R20/21/22; C: R34; Sens.: R43; N: R51/53; Xn: R68**Classification under CLP:** Aquatic Chronic 2: H411; Muta. 2: H341; Skin Corr. 1B: H314; Skin Sens. 1: H317**Most important adverse effects:** Harmful by inhalation, in contact with skin and if swallowed. Causes burns. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of irreversible effects.**2.2. Label elements****Label elements under CLP:****Hazard statements:** H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H341: Suspected of causing genetic defects.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

SAFETY DATA SHEET

PROV 500

Page: 2

Hazard pictograms: GHS05: Corrosion
GHS07: Exclamation mark
GHS08: Health hazard
GHS09: Environmental



Precautionary statements: P202: Do not handle until all safety precautions have been read and understood.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P264: Wash skin thoroughly after handling.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+313: IF exposed or concerned: Get medical advice/attention.
P321: Specific treatment (see manufacturers information on this label).

Label elements under CHIP:

Hazard symbols: * Dangerous for the environment.
Corrosive.



Risk phrases: * R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R34: Causes burns.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R68: Possible risk of irreversible effects.

Safety phrases: * S2: Keep out of the reach of children.
S24: Avoid contact with skin.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: *

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

[cont...]

SAFETY DATA SHEET

PROV 500

Page: 3

3.2. Mixtures

*** Hazardous ingredients:**

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

EINECS	CAS	CHIP Classification	CLP Classification	Percent
500-033-5	25068-38-6	Xi: R36/38; Sens.: R43; N: R51/53	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	30-40%

BISPHENOL-F EPICHLORHYDRIN RESIN: MW<700

-	9003-36-5	Xi: R38; Sens.: R43; N: R51/53	Skin Irrit. 2: H315; Skin Sens. 1: H317; Eye Irrit. 2: H319; Aquatic Chronic 2: H411	10-20%
---	-----------	--------------------------------	--	--------

1,6-HEXANDIOLDIGLYCIDYLETHER

240-260-4	16096-31-4	Xi: R36/38; Sens.: R43; -: R52/53	Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	10-20%
-----------	------------	-----------------------------------	--	--------

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

220-666-8	2855-13-2	Xn: R21/22; C: R34; Sens.: R43; -: R52/53	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	3-10%
-----------	-----------	--	--	-------

BENZYL ALCOHOL

202-859-9	100-51-6	Xn: R20/22	Acute Tox. 4: H332; Acute Tox. 4: H302	1-3%
-----------	----------	------------	--	------

2,2'-IMINODIETHYLAMINE

203-865-4	111-40-0	Xn: R21/22; C: R34; Sens.: R43	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317	1-3%
-----------	----------	--------------------------------	---	------

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

202-013-9	90-72-2	Xn: R22; Xi: R36/38	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-3%
-----------	---------	---------------------	--	------

PHENOL

203-632-7	108-95-2	T: R23/24/25; C: R34; Xn: R48/20/21/22; Xn: R68	Muta. 2: H341; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Skin Corr. 1B: H314	1-3%
-----------	----------	--	--	------

1,3-BENZENEDIMETHANAMINE

216-032-5	1477-55-0	C: R34; Xn: R20/22; Sens.: R43; -: R52/53	Skin Corr. 1B: H314; Aquatic Chronic 3: H412; Acute Tox. 4: H302; Skin Sens. 1: H317; Acute Tox. 3: H331	1-3%
-----------	-----------	--	--	------

Section 4: First aid measures

[cont...]

SAFETY DATA SHEET

PROV 500

Page: 4

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Corrosive. May cause sensitization by skin contact.

Eye contact: Corrosive.

Ingestion: Harmful if swallowed.

Inhalation: Harmful by inhalation.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder. Water spray. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Pick up mechanically. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

[cont...]

SAFETY DATA SHEET

PROV 500

Page: 5

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Building and construction work (SU19).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2,2'-IMINODIETHYLAMINE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	4.3 mg/m ³	-	-	-

PHENOL

UK	2 ppm	4 ppm	-	-
----	-------	-------	---	---

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: * Breathing protection is required in inadequately ventilated places.

Hand protection: * Nitrile gloves. Breakthrough time of the glove material < 1 hour.

Eye protection: Tightly fitting safety goggles.

Skin protection: Protective clothing.

Environmental: No special requirement.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Various

Odour: Perceptible odour

Solubility in water: Insoluble

Relative density: 1.44

[cont...]

SAFETY DATA SHEET

PROV 500

Page: 6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: No specific recommendations.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Acids.

10.6. Hazardous decomposition products

Haz. decomp. products: No data available.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg
ORL	RAT	LD50	1230	mg/kg

2,2'-IMINODIETHYLAMINE

IPR	RAT	LD50	74	mg/kg
ORL	MUS	LD50	970	mg/kg
ORL	RAT	LD50	970	mg/kg

[cont...]

SAFETY DATA SHEET

PROV 500

Page: 7

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

ORL	RAT	LD50	1200	mg/kg
SKN	RAT	LD50	1280	mg/kg

PHENOL

ORL	MUS	LD50	270	mg/kg
ORL	RAT	LD50	317	mg/kg
SCU	RAT	LD50	460	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM ING	Hazardous: calculated
Corrosivity	OPT INH DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Corrosive. May cause sensitization by skin contact.

Eye contact: Corrosive.

Ingestion: Harmful if swallowed.

Inhalation: Harmful by inhalation.

Delayed / immediate effects: No data available.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Insoluble in water. Heavier than water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environment.

[cont...]

SAFETY DATA SHEET

PROV 500

Page: 8

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: * UN3259

14.2. UN proper shipping name

Shipping name: AMINES, SOLID, CORROSIVE, N.O.S.
(BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}); BISPHENOL-F
EPICHLORHYDRIN RESIN: MW<700; 1,6-HEXANDIOLDIGLYCIDYLETHER)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: * II

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: * Yes

14.6. Special precautions for user

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H301: Toxic if swallowed.

[cont...]

SAFETY DATA SHEET

PROV 500

Page: 9

H302: Harmful if swallowed.

H311: Toxic in contact with skin.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H332: Harmful if inhaled.

H341: Suspected of causing genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R20/22: Harmful by inhalation and if swallowed.

R21/22: Harmful in contact with skin and if swallowed.

R22: Harmful if swallowed.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R34: Causes burns.

R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

R43: May cause sensitisation by skin contact.

R48/20/21/22: Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R68: Possible risk of irreversible effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.