

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PROV 200

Product code: 40292

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: A Chemical anchoring application

1.3. Details of the supplier of the safety data sheet

Company name: Proventure Solutions Ltd

Lakeside

Wanes Blades Road

Lathom

Ormskirk

L40 4BN

England

Tel: 01704 897 015

Email: sales@proventure.co.uk

1.4. Emergency telephone number

Emergency tel: 01704 879 015

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Sens.: R43; -: R52/53

Classification under CLP: Eye Irrit. 2: H319; Aquatic Chronic 3: H412; Skin Sens. 1: H317

Most important adverse effects: May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CLP:

Hazard statements: H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



SAFETY DATA SHEET

PROV 200

Page: 2

Precautionary statements: P264: Wash skin thoroughly after handling.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.

S24: Avoid contact with skin.

S37: Wear suitable gloves.

2.3. Other hazards

Other hazards: Not applicable.

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHYLVINYLBENZENE

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|-----------|------------|-----------------------------------|---|---------|
| 248-846-1 | 28106-30-1 | Xn: R20; Xi: R36/37/38; N: R51/53 | Acute Tox. 4: H302+312+332; STOT SE 3: H335; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315 | 3-10% |

2-ETHYLHEXYL BENZOATE

| | | | | |
|-----------|-----------|--------|-------------------------|------|
| 226-641-8 | 5444-75-7 | -: R53 | Aquatic Chronic 4: H413 | 1-3% |
|-----------|-----------|--------|-------------------------|------|

POLY(OXY.1,2-ETHANDIYL),A,A'-[[[4-METHYLPHENYL]IMINO]DI-2,1-ETHANDIYL]BIS[OMEGA-HYDROXY-

| | | | | |
|---|-------------|------------------|--------------------------------------|------|
| - | 103671-44-9 | Xn: R22; Xi: R41 | Eye Dam. 1: H318; Acute Tox. 4: H302 | 1-3% |
|---|-------------|------------------|--------------------------------------|------|

[cont...]

SAFETY DATA SHEET

PROV 200

Page: 3

DIBENZOYL PEROXIDE

| | | | | |
|-----------|---------|-----------------------------------|---|------|
| 202-327-6 | 94-36-0 | E: R3; O: R7; Xi: R36; Sens.: R43 | Skin Sens. 1: H317; Org. Perox. B: H241; Eye Irrit. 2: H319 | 1-3% |
|-----------|---------|-----------------------------------|---|------|

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

| | | | | |
|-----------|------------|-------------------------------------|---|-----|
| 265-199-0 | 64742-95-6 | Xn: R65; -: R10; Xi: R37; N: R51/53 | Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411 | <1% |
|-----------|------------|-------------------------------------|---|-----|

N,N-DIMETHYL-P-TOLUIDINE

| | | | | |
|-----------|---------|----------------------------------|--|-----|
| 202-805-4 | 99-97-8 | T: R23/24/25; Xn: R33; -: R52/53 | Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Aquatic Chronic 3: H412 | <1% |
|-----------|---------|----------------------------------|--|-----|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: If conscious, give half a litre of water to drink immediately. Do not induce vomiting. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be loss of consciousness.

Inhalation: There may be loss of consciousness.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Dry chemical powder. Carbon dioxide. Foam. Do not use halons.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Sealed, heated containers can pressurise leading to explosion. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

[cont...]

SAFETY DATA SHEET

PROV 200

Page: 4

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container. Wash the area with water.

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Keep away from Heat and sources of ignition. Comp. B = Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Ensure lighting and electrical equipment are not a source of ignition. Store in cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Building and construction work (SU19).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIBENZOYL PEROXIDE

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | | 15 min. STEL | |
|-------|---------------------|--------------|--------------|--------------|
| | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
| UK | 5 mg/m ³ | - | - | - |

8.1. DNEL/PNEC Values

Hazardous ingredients:

DIBENZOYL PEROXIDE

| Type | Exposure | Value | Population | Effect |
|------|----------|-----------------|--------------------|----------|
| DNEL | Oral | 1.65 mg/kg bw/d | General Population | Systemic |

[cont...]

SAFETY DATA SHEET

PROV 200

Page: 5

| | | | | |
|------|------------|-----------------------|--------------------|----------|
| DNEL | Dermal | 3.3 mg/kg bw/d | General Population | Systemic |
| DNEL | Inhalation | 2.9 mg/m ³ | General Population | Systemic |

8.2. Exposure controls

Engineering measures: Ensure all engineering measures mentioned in section 7 of SDS are in place.

Respiratory protection: Breathing protection is required in inadequately ventilated places. Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: * Protective gloves. Viton gloves. EN 374 Recommended thickness of material >0.4 mm
Breakthrough time of the glove material > 8 hours. Before use, the protective gloves should be tested in any case for its specific work-station suitability.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Various

Odour: Characteristic odour

Oxidising: Oxidising (by EC criteria)

Solubility in water: Insoluble

Relative density: 1.61

VOC g/l: 0.66

9.2. Other information

Other information: * Solid suspension - classified as non-flammable according to results from Test N.1 test method for readily combustible solids.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. May polymerise on heating.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Reducing agents. Acids. Alkali. Heavy metal compounds. Organic peroxide. Oxidising agents.

[cont...]

SAFETY DATA SHEET

PROV 200

Page: 6

10.6. Hazardous decomposition products

Haz. decomp. products: If exposed to high temperatures it will emit hazardous fumes and smoke.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIBENZOYL PEROXIDE

| | | | | |
|---------|-----|------|------|-------|
| ORL | RAT | LD50 | 5000 | mg/kg |
| VAPOURS | RAT | LD50 | 24.3 | mg/kg |

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

| | | | | |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 8400 | mg/kg |
|-----|-----|------|------|-------|

N,N-DIMETHYL-P-TOLUIDINE

| | | | | |
|-----|-----|------|-----|-------|
| IPR | MUS | LD50 | 212 | mg/kg |
|-----|-----|------|-----|-------|

Relevant effects for mixture:

| Effect | Route | Basis |
|---------------|-------|-----------------------|
| Sensitisation | DRM | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be loss of consciousness.

Inhalation: There may be loss of consciousness.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

DIBENZOYL PEROXIDE

| | | | |
|-------------------------------------|-----------|--------|------|
| ALGAE | 72H ErC50 | 0.0711 | mg/l |
| Daphnia magna | 48H EC50 | 0.110 | mg/l |
| RAINBOW TROUT (Oncorhynchus mykiss) | 96H LC50 | 0.0602 | mg/l |

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

[cont...]

SAFETY DATA SHEET

PROV 200

Page: 7

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. Small quantities of the product can be mixed and allowed to cure, then can be disposed as solid waste.

Waste code number: 08 04 12

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H226: Flammable liquid and vapour.

H241: Heating may cause a fire or explosion.

H301: Toxic if swallowed.

H302: Harmful if swallowed.

H302+312+332: Harmful if swallowed, in contact with skin or if inhaled.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

[cont...]

SAFETY DATA SHEET

PROV 200

Page: 8

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H335: May cause respiratory irritation.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

H413: May cause long lasting harmful effects to aquatic life.

R3: Extreme risk of explosion by shock, friction, fire or other sources of ignition.

R7: May cause fire.

R10: Flammable.

R20: Harmful by inhalation.

R22: Harmful if swallowed.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R33: Danger of cumulative effects.

R36/37/38: Irritating to eyes, respiratory system and skin.

R36: Irritating to eyes.

R37: Irritating to respiratory system.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53: May cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

ENVIRONMENTAL CARE: Please do not dispose of uncured material. If disposing please mix any waste product to its cured state.