



## GRATING FASTENER SYSTEM

The GRATF-ZP grating fastener system combines a shot fired threaded stud and grating disc to secure open mesh flooring in dry and non-corrosive indoor environments.

The threaded stud and grating disc are zinc plated. It is an alternative to the Hilti X-FCM grating fastener disc. Full test data available.

It is suitable for fixing grids up to 40mm thick, with a mesh dimension no less than 18x18mm, in base steel at least 6mm thick.

### GRATING DISC - ZINC PLATED



Item	thread length	head diameter	grid thickness
GRATF25ZP	25mm	50mm	25mm
GRATF30ZP	30mm	50mm	30mm
GRATF40ZP	40mm	50mm	40mm


### BENEFITS

- **TOTAL MOBILITY**  
no electrical power required
- **FAST, ECONOMICAL AND CONVENIENT**  
up to 120 grating fastenings per hour by one user
- **LOCKING TABS ON THE GRATING DISC**  
help prevent the fastener working loose
- **NON SLIP SURFACE**  
no tripping hazard

### APPLICATIONS

- food industry
- steel industry
- power plants
- public facilities

### THREADED STUD - ZINC PLATED



GRATF8-ZP threaded stud M8-30/15, zinc plated  
thread length: 15mm, overall length: 30mm

### P370-GR GRATING TOOL



**P370-GR Grating tool**  
Powder actuated tool for fastening gratings using the M8-30/15 threaded stud and GRATF grating disc.

The GRATF grating fastener system can also be used with the Hilti DX cartridge tool range.

Please contact us for more information on  
01704 897 015 or visit [www.proventure.co.uk](http://www.proventure.co.uk)

