

PROV 200

Page: 1

Compilation date: 13/01/2012

Revision date: 30/09/2019

Revision No: 5

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PROV 200 Product code: 40292

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: A Chemical anchoring application

1.3. Details of the supplier of the safety data sheet

Company name: Proventure Solutions Limited

Lakeside

Wanes Blades Road

- Ormskirk
- L40 4BN

Tel: +44 (0)1704 894 015

Email: sales@proventure.co.uk

1.4. Emergency telephone number

Emergency tel: 01704 897 015

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: * Eye Irrit. 2: H319; Skin Sens. 1: H317

Most important adverse effects: May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Label elements:	
UFI:	EH7U-84Q5-E00P-GXME
Hazard statements:	* H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
Hazard pictograms:	GHS07: Exclamation mark



PROV 200

Signal words:	Warning
Precautionary statements:	* P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352: IF ON SKIN: Wash with plenty of water.
	P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P362+P364: Take off contaminated clothing and wash it before reuse.
Haz. ingredients (label):	2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE; METHACRYLIC ACID, MONOESTER
	WITH PROPANE-1,2-DIOL; DIBENZOYL PEROXIDE; 1,1'-(P-TOLYLIMINO)DIPROPAN-2
	-OL; P-BENZOQUINONE
2.3. Other hazards	

Other hazards: Not applicable.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

* Hazardous ingredients:

2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE - REACH registered number(s): 01-2119969287-21

		-				
EINECS	CAS	PBT / WEL	CLP Classification	Percent		
203-652-6	109-16-0	-16-0 - Skin Sens. 1: H317				
METHACRYLIC ACID, MONOESTER WITH PROPANE-1,2-DIOL - REACH registered number(s): 01-2119490226-37						
248-666-3 27813-02-1 - Eye Irrit. 2: H319; Skin Sens. 1: H317 3-10%						
DIBENZOYL PEROXIDE - REACH registered number(s): 01-2119511472-50-XXXX						
202-327-6	94-36-0	-	Skin Sens. 1: H317; Org. Perox. B: H241; Eye Irrit. 2: H319	1-3%		
1,1'-(P-TOLYLIMINO)DIPROPAN-2-OL - REACH registered number(s): 01-2119980937-17-XXXX						
254-075-1	38668-48-3	-	Acute Tox. 2: H300; Eye Irrit. 2: H319;	<1%		

P-BENZOQUINONE

203-405-2	106-51-4	-	Acute Tox. 3: H331; Acute Tox. 3: H301;		
			Eye Irrit. 2: H319; STOT SE 3: H335;		
			Skin Irrit. 2: H315; Aquatic Acute 1:		
			H400		

Aquatic Chronic 3: H412

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Page: 2

PROV 200

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

PROV 200

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): Building and construction work (SU19).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIBENZOYL PEROXIDE

Workplace e	exposure limits:		Respirable dust:	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	-	-	-

P-BENZOQUINONE

LIK 0.45 mg/m3 1.3 mg/m3 -			UK	0.45 mg/m3	1.3 mg/m3	-	-
----------------------------	--	--	----	------------	-----------	---	---

DNEL/PNEC Values

Hazardous ingredients:

2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	13.9mg/kg	Workers	Local
DNEL	Inhalation	48.5mg/m3	Workers	Local

METHACRYLIC ACID, MONOESTER WITH PROPANE-1,2-DIOL

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	14.7 mg/m³	Workers	Systemic
DNEL	Dermal	4.2 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	8.8 mg/m³	General Population	Systemic
DNEL	Dermal	2.5 mg/kg bw/day	General Population	Systemic
DNEL	Oral (repeated dose)	2.5 mg/kg bw/day	General Population	Systemic

PROV 200

Page: 5

DIBENZOYL PEROXIDE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	39 mg/m³	Workers	Systemic
DNEL	Dermal (repeated dose)	13.3 mg/kg bw/day	Workers	Systemic
DNEL	Dermal	34 µg/cm²	Workers	Local
DNEL	Oral (repeated dose)	2 mg/kg bw/day	General Population	Systemic

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Breathing protection is required in inadequately ventilated places. Gas/vapour filter, type
	A: organic vapours (EN141).
Hand protection:	Nitrile gloves. Viton gloves. Wear solvent proof gloves. EN 374 Recommended
	thickness of material >0.4 mm. Breakthrough time of the glove material > 8 hours. As the
	product is a preperation of several substances, the resistance of the glove material can
	not be calculated in advance and has therefore to be checked prior to the application.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Paste
Colour:	Various
Odour:	Characteristic odour
Oxidising:	Not applicable.
Solubility in water:	Insoluble
Relative density:	1.67 VOC g/l: 0.66
9.2. Other information	

Other information: Solid suspension - classified as non-flammable according to results from Test N.1 test method for readily combustible solids.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

PROV 200

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DIBENZOYL PEROXIDE

ORL	RAT	LD50	2000	mg/kg
VAPOURS	RAT	LD50	24.3	mg/kg

1,1'-(P-TOLYLIMINO)DIPROPAN-2-OL

ORAL RAT LD50	25	mg/kg
---------------	----	-------

P-BENZOQUINONE

ORL	MUS	LD50	25	mg/kg
ORL	RAT	LD50	130	mg/kg
SCU	MUS	LD50	93800	µg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

PROV 200

Page: 7

Ecotoxicity values: Catalyst Comp B

Species	Test	Value	Units
ALGAE	72H ErC50	>60	mg/l
Daphnia magna	48H EC50	>11	mg/l
FISH	48H EC50	>7	mg/l
FISH	96H LC50	>100	mg/l

Hazardous ingredients:

DIBENZOYL PEROXIDE

ALGAE	72H ErC50	0.0711	mg/l
Daphnia magna	48H EC50	0.110	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	0.0602	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
Waste code number:	08 04 09
Disposal of packaging:	Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

PROV 200

Page:	8
-------	---

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	Active Oxygen Content of Catalyst Component 0.99%
	* indicates text in the SDS which has changed since the last revision.
	MAL Code: 1-5
Phrases used in s.2 and s.3:	H241: Heating may cause a fire or explosion.
	H300: Fatal if swallowed.
	H301: Toxic if swallowed.
	H315: Causes skin irritation.
	H317: May cause an allergic skin reaction.
	H319: Causes serious eye irritation.
	H331: Toxic if inhaled.
	H335: May cause respiratory irritation.
	H400: Very toxic to aquatic life.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.