



## GRATING FASTENER SYSTEM

The GRATF-G grating fastener system combines a shot fired threaded stud and grating disc to secure open mesh flooring in corrosive and outdoor environments.

The grating disc is Duplex coated with 440 hours salt spray resistance before the appearance of red rust. It is an alternative to the Hilti X-FCM-F grating fastener disc. It is suitable for fixing grids up to 50mm thick, with a mesh dimension no less than 18x18mm, in base steel at least 6mm thick.

The threaded stud is Zinc Nickel coated with 1,000 hours salt spray resistance before the appearance of red rust.

Full test data available.

### BENEFITS


- HIGH CORROSION PROTECTION FOR HARSH ENVIRONMENTS
- ENHANCED SALT SPRAY RESISTANCE before appearance of red rust
- TOTAL MOBILITY no electrical power required
- FAST, ECONOMICAL AND CONVENIENT up to 120 grating fastenings per hour by one user
- LOCKING TABS ON THE GRATING DISC help prevent the fastener working loose
- NON SLIP SURFACE no tripping hazard

### APPLICATIONS

- chemical and oil industries
- off shore and ship building
- food industry
- water supply treatment works
- steel industry
- power plants
- public facilities


Please contact us for more information on 01704 897 015 or visit [www.proventure.co.uk](http://www.proventure.co.uk)

### GRATING DISC - DUPLEX



Item	shank length	head diameter	grid thickness
GRATF25G	22mm	50mm	25mm
GRATF30G	27mm	50mm	30mm
GRATF40G	37mm	50mm	40mm
GRATF50G	47mm	50mm	50mm

### THREADED STUD - ZINC NICKEL



GRATF8-G threaded stud M8-30/15, Zinc Nickel thread length: 15mm, overall length: 30mm

### P370-GR GRATING TOOL



#### P370-GR Grating tool

Powder actuated tool for fastening gratings using the M8-30/15 threaded stud and GRATF grating disc.

The GRATF grating fastener system is compatible with the Hilti DX cartridge tool range.

